

LANZA		Posición	CAUDAL DE LANZA		ALCANCE EFECTIVO	
			GPM	LPM	Pies	Metros
VIPER SELECT		1	5	19	62	19
		2	10	37	85	26
		3	24	90	98	30
		4	40	150	108	33
	SG1560	1	15	50	62	19
		2	30	125	85	26
		3	50	200	98	30
		4	60	230	108	33
	SG3012	1	30	115	85	26
		2	60	230	112	34
		3	95	360	131	40
		4	125	475	141	43
	SG7515	1	75	265	118	36
		2	100	380	138	42
		3	125	500	144	44
		4	150	600	148	45
	SG9520	1	95	350	128	39
		2	125	500	141	43
		3	150	600	148	45
		4	200	800	154	47
	SG12250	1	125	500	131	40
		2	150	600	144	44
		3	200	800	151	46
		4	250	1000	157	48
VIPER AUTOMATIC			23	90	82	25
			38	150	131	40
			70	275	138	42
			145	550	144	44
VIPER CONSTANT			30	115	85	26
			95	360	135	41
			125	475	144	44
			210	800	157	48
VIPER INDUSTRIAL			15	57	82	25
			30	114	92	28
			45	170	101	31
			60	227	112	34
			95	360	131	40
			95	360	118	36
	ST 2510		110	416	125	38
			39	150	82	25
	VTE 1550		95	360	95	29
			95	360	95	29
BLUE DEVIL		1	5	25	59	18
		2	15	50	82	25
		3	30	100	92	28
		4	50	175	101	31
		1	13	50	82	25
		2	23	90	88	27
		3	30	115	92	28
		1	15	55	82	25
		2	30	110	92	28
		3	45	170	101	31
		4	60	225	112	34
		1	30	115	85	26
		2	60	230	112	34
		3	95	360	131	40
		4	125	470	141	43
		1	30	115	85	26
		2	60	230	112	34
		3	95	360	131	40
		4	125	470	141	43
		5	150	560	148	45
		1	60	230	112	34
		2	75	280	118	36
		3	95	360	131	40
		4	125	470	141	43
		5	150	560	148	45
		1	75	280	118	36
		2	95	360	138	42
		3	125	470	144	44
		4	150	560	148	45
		1	95	360	128	39
		2	125	470	141	43
		3	150	560	148	45
		4	200	750	154	47
		1	125	470	131	40
		2	150	560	144	44
		3	200	750	151	46
		4	950	950	157	48