


RUP 502-U

Lifting and lowering evacuation device

EN 1496/B



The RUP502-U lifting and lowering evacuation device is a rescue equipment component. Using the device, an injured person can be raised from a lower level to a higher level or lowered from a higher level to a lower level. The descent distance must not exceed 2 meters.

Winch equipped with automatic friction brake.

SPECIAL FEATURES



PARAMETERS

WLL working load limit	140 kg
MBS minimum breaking strength	20 kN
Safety Factor	10:1

KIT INCLUDES

Spring absorber	SDW
-----------------	-----

Długość korby - Wariant 1	150 mm
Długość korby - Wariant 2	300 mm
Siła wymagana do wyciągania ładunku w wariant 1	5,6 kg
Siła wymagana do wyciągania ładunku w wariant 2	11,6 kg
Przełożenie mechanizmu przekładni	5:1

CONSTRUCTION

Material	steel
----------	-------

Finishing	galvanization
-----------	---------------

MECHANISM

Material	steel
Finishing	galvanization

POKRYWA

Material	plastic
Color	orange

ROPE

Material	steel
Finishing	galvanization
Rope diameters $\varnothing$	6,3 mm

PROTEKT

PROTEKT Grzegorz Łaskiewicz Spółka z o. o. Starorudzka Str. 9, 93-403 Łódź, POLEN
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

WWW.PROTEKT.PL

HANDELSABTEILUNG 6 Skromna St., 93-405 Łódź, POLEN
Telefon +48 42 29-29-500, export@protekt.com.pl, Fax +48 42 680-20-93