

RUP 503-B

Hand Lifting Device

EN 1496/B



- RUP 503-B is a winch equipped with clamp for mounting on tripod leg. The winch is equipped with six-strand steel cable with natural fibre kern, available in options of 25 m, 35 m, 45 m, 50 m in length and 6.3 mm in diameter;
- RUP 503-B is a component of rescue equipment. Using the device, a casualty can be lifted from a lower level onto a higher level or vice-versa. The descent distance cannot be more than 2 m;
- With the ratio used in the mechanism it is possible to make one turn of the drum per 7.2 turns of the winch's crank;
- Crank arm can be disassembled for easier transport;
- The RUP 503-B evacuation device of the series complies with EN 1496/B;

SPECIAL FEATURES



PARAMETERS

WLL working load limit	200 kg
MBS minimum breaking strength	21 kN
Safety Factor	10:1

KIT INCLUDES

Spring absorber	SDW
Block	PL 101
Długość korby - Wariant 1	300 mm
Siła wymagana do wyciągania ładunku w wariantcie 1	10 kg
Przełożenie mechanizmu przekładni	7,2:1

CONSTRUCTION

Material	steel
----------	-------

Finishing	galvanization
-----------	---------------

COVER

Material	steel
Manufacture	powder coating

ROPE

Material	steel
Finishing	galvanization
Rope diameters Ø	6,3 mm

PROTEKT

PROTEKT Grzegorz Łaskiewicz Spółka z o. o. Starorudzka Str. 9, 93-403 Łódź, POLEN
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

WWW.PROTEKT.PL

HANDELSABTEILUNG 6 Skromna St., 93-405 Łódź, POLEN
Telefon +48 42 29-29-500, export@protekt.com.pl, Fax +48 42 680-20-93

RUP 503-B

Hand Lifting Device

VARIANTS

ref. no.	length [m]
AT 053-B 25	25
AT 053-B 35	35
AT 053-B 45	45
AT 053-B 50	50